



M材質	Inner Hardness I.H內部硬度	Surface Hardness S.H表面硬度	Heat Treatment 熱處理
FDAC	HRC38 $\pm$ 2°	HV1000 $\pm$ 100°	氮化處理 Nitrided
	HRC52 $\pm$ 2°	HRC52 $\pm$ 2°	真空處理 Vacuumed

d	容許差 Tolerance	D	容許差 Tolerance	Catalog No.			H	容許差 Tolerance
				Type	d1	容許差 Tolerance		
4	-0.01 -0.02	8	0 -0.2	JH008	1.5~2	+0.01 0	6	0 -0.02
4.5					2~3			
5		2~3.5						
6		2~4.5						
6.5		2~5						
7		2~5.5						
8		2~6.5						
9	2~7.5	+0.02 0			8			
10	2~8							
12	2~10	+0.02 0			8~12	0 -0.03		
13	內孔尺寸 2mm以上 任意指定							
14								
15								
16								
20								
25								
30	8~12							

●Order: Catalog No. [D] × [H] × [d] × [d1] × [L]

- 備注: 1.圖面以外規格可定制。  
 2.一次單一尺寸訂購50祇以上價格另議。  
 3.長度指定切短少於5m/m。  
 Remark: 1.Special product is available.  
 2.Price is negotiable if quantity of each size is more than 50 in one order.  
 3.Length appointed be cut less than 5mm.

d	d1	L																				
		75	100	125	150	175	200	225	250	275	300	350	400	450	500	550	600	700	800	900	1000	
2.5	1~1.2																					
3	1.3~1.6																					
3.5	1.6~1.9																					
3.5	2,2.2																					
4	2,2.5																					
5	2.5,3																					
6	3,3.5																					
7	3.5,4																					
8	3.5,4,5																					
9	4,5,6																					
10	4,5,6																					
12	5,6,8																					
13	5,6,8,10																					
14	5,6,8,10																					
15	5,6,8,10																					
16	6,8,10,12																					
20	8,10,12,16																					
25	10,12,16																					
30	10,12,16,20																					

- 備注: 1.目錄標示之價格, 如V部單壁薄小於0.7mm, 內孔小於2mm,則另行報價。  
 2.目錄上所標d1處尺寸在1.9以內, 其內孔e部在20mm以內為基礎。  
 3.內孔在2mm以內請預留長度1mm以內, 內孔2mm以上請預留長度3mm以內  
 Remark: 1.If the ply of "V" part is below 0.7mm, "d1" is below 2mm, the price will be additional price.  
 2."e" Part is below 20mm base on "d1" below 1.9.  
 3.Please set aside below 1mm's length when "d1" is below 2mm, set aside below 3mm's length when "d1" is above 2mm.